

Key features	Picture
The Intelligent IP Video Monitor SIP 2.0 Video Intercom and Unlock Screen: 1024x600 Resolution Operating System: Embedded Linux Network: 10/100Mbps Ethernet Storage: Supports MicroSD up to 512GB Two-Way Audio Communication Remote Access and Control ONVIF / RTSP Compatibility Live views of door stations & cameras up to 8pcs IP Camera Connection: ONVIF Protocol Personalized wallpaper & Ringtones Dual control (Door/Gate) Do not disturb Night mode Power: PoE IEEE 802.3af DC15V 0.8A	

Specifications	
Operation system	Embedded linux
Display resolution	1024x600
Operation method	7" touch screen
Audio intercom mode	Full duplex
Monitor connection	10
Outdoor station connection + CCTV camera connection	8
Wire network	10 / 100 Mbps adaptive ethernet
External memory	Micro SD card, up to 512GB
Support pixels	Main stream support Max 2MP 25FPS camera Sub stream support Max 1MP 30FPS camera
Video compression standard	H.265 (default), H.264
Network protocol	TCP/IP, RTSP, SIP 2.0
Internal memory	Support
Video recording	Support
Customized ringtone	AAC

Customized background	Support
Power supply	POE IEEE 802.3af / DC15V 0.8A
Power consumption	7W(Max), 3W(Standby)
Working temperature	-10°C to +50°C
Working humidity	10% - 90%
Product size	188x136x22mm

Typical Application

