

Smart IP Video Intercom Doorbell

DIGIVED011B SR

DIGIVISION

Key Features	Picture
• Display: 4.3" Screen with 480*272 resolution for clear visuals. • Cameras: HD cameras at 2MP resolution with a 125° wide viewing angle. • WDR Technology: Enhances image quality by balancing light and dark areas. • Audio: Full Duplex Communication for clear two-way audio. • Video Compression: Supports H.265 & H.264. • Multiple Entry Methods: IC card (13.56MHz), ID card (125kHz), PIN code, mobile app, QR code, and call. • Anti-Spoofing: Protects against unauthorized access using photos or videos. • User Capacity: Supports up to 9,999 users and 20,000 cards. • Security Features: Tamper alarm and EXIT button support. • Control Capabilities: Controls gate and door locks, with WG input and output supported. • Integration: Easy integration with other SIP devices using SIP 2.0 protocol. • Durable Design: IP65 & IK07 rated for protection. • Mounting Options: Flexible surface or flush mounting. • Power Supply: PoE or DC12-15V.	

Specifications	
Apartments	9999
Operation system	Embedded linux operation system
Angle of view	125°
Video compression standard	H.265 (default), H.264
Noise reduction	3D noise reduction
Night vision	Smart IR
Pixel	Main stream: 1920x1080p, 720p, Sub stream: 640x360
Audio intercom	Full duplex
Network interface	10M / 100M adaptive belt POE
Network protocol	TCP/IP, RTSP, SIP 2.0
Lock	NO/NC (MAX AC/DC30V 4A)
GATE	NO (MAX AC/DC30V 4A)
Wiegand 26/34 output	Support
Wiegand 26/34 input	Support
Exit button	Support
Door contact input	Support

ID&IC Card	125KHZ (ID) / 13.56MHZ (IC)
	Em marine (ID) / Mifare (IC)
	Supports ISO/IEC 18000-2 type A (ID)
	Supports ISO/IEC 14443 type A 106kb/s (IC)
	Number of cards supported: 20000
	Card reading distance: ≤2cm
Unlock Mode	IC card (13.56MHz), ID card (125kHz), PIN code, mobile app, QR code, and call
Protection grade	IK07; IP65
Power supply	PoE or DC12-15V
Working temperature	-30°C to +60°C(-22°F-140°F)
Working humidity	10%RH – 90%RH (non-condensing)
Flush box dimensions	249.6x109.5x24.5mm
Product size	268x127.5x27.3mm

Typical Application

